



KATI

9016 3000K/CRI80 on/off



| | | | |
|-------------------------|------------------|----------------------------------|-------------------|
| Beamangle | 60° | Input current | 350mA |
| CIE Flux Codes | 93 97 99 100 101 | IP | IP44 |
| Colour Deviation (SDCM) | 3 sdcM | Color | White |
| Colour Temperature | 3000K | Led type | COB |
| Max. connected Load | 2x7W | Lumen Maintenance | L80B10 bij 40.000 |
| Connected Voltage | 220-240V | Lumen/W | 135lm/W |
| CRI | 90 | Luminous flux of luminaire | 1120lm |
| Cut Out Dimensions | 150x72 | Material Housing | Aluminium |
| Dim | No | Material Lens/Reflector/Diffusor | PC |
| Dimensions | 160x75x90 | Mounting Type | Recessed |
| Energy Efficiency Class | D | PF | 0,9 |
| Forward Voltage | 17-20V | Protection Class | I |
| Frequency | 50-60Hz | Recess Depth | 75 |
| IK | 07 | UGR | 19 |
| | | Weight | 350g |

Reference : 000003777

Product Description

Double recessed downlighter, double the atmosphere. Coupling both light sources in one luminaire creates a unique atmosphere. An ingenious system ensures that the mounting screws are discreetly integrated into the downlighter. Known for its directivity, popular for its combination with optimum light emission. This makes the KATI very popular in the commercial market such as retail. Available in 3000K and 4000K. Dimensions: 160x75x90. Available in RAL9005 and RAL9016. Standard in on/off, dimmable possible in dali, dali push, triac or 1-10V.