



FLO ROUND 180

3000K/CRI80 on/off 9005



Beamangle	120	IP	IP54
CIE Flux Codes	49 78 95 100 100	Input current	350mA
CRI	80	Color	RAL9005
Colour Deviation (SDCM)	3 sdcM	Led type	SMD
Colour Temperature	3000K	Lumen Maintenance	L80B10 bij 50.000
Max. connected Load	12W	Lumen/W	135lm/W
Connected Voltage	220-240V	Luminous flux of luminaire	1200lm
Dim	No	Material Housing	Diecast aluminium
Dimensions	Ø180x38,5	Material Lens/Reflector/Diffusor	PMMA
Energy Efficiency Class	D	Mounting Type	Plafond
Forward Voltage	18-30V	PF	0,9
Frequency	50-60Hz	Protection Class	I
IK	07	UGR	24

Product Description

FLO ROUND is the surface-mounted version of the FL product range. This surface-mounted downlight has a sleek modern look and fits tightly against the ceiling or wall. The frosted diffuser provides an even light distribution with a 120° beam. The FLO is widely applicable from residential (kitchen, hallway, attic,...) to office lighting (corridors, toilets, stands,...). Available in four types: 180 (Dimensions: Ø180x14), 240 (Dimensions: Ø240x20), 300 (Dimensions: Ø300x14) and 600 (Dimensions: Ø600x14). Available in 3000K or 4000K. Standard on/off. Dimmable in dali, dali push, triac and 1-10V. This panel is available in RAL9005 and RAL9016.

Reference : 000002807