



BOLD 25

3000K/CRI80 on/off 9005



Beamangle	60°	IP	IP54
CIE Flux Codes	85 99 100 100 100	Input current	600mA
CRI	90	Color	RAL9005
Colour Deviation (SDCM)	3 sdcM	Led type	COB
Colour Temperature	3000K	Lumen Maintenance	L80B10 bij 50.000
Max. connected Load	25W	Lumen/W	135lm/W
Connected Voltage	220-240V	Luminous flux of luminaire	2500lm
Dim	No	Material Housing	Aluminium
Dimensions	Ø110x120	Material Lens/Reflector/Diffusor	Glass
Energy Efficiency Class	D	Mounting Type	Plafond
Forward Voltage	30-40V	PF	0,9
Frequency	50-60Hz	Protection Class	I
IK	02	UGR	<19
		Weight	800g

Product Description

The Bold is just that little bit extra. Bring your space to life and mix-and-match this powerful downlighter. The simple finish, refined with elegance, makes the Bold extremely versatile. The powerful light output ensures targeted illumination. The cylindrical design ensures that the Bold fits in with many modern living styles. Whether in the commercial market or in the living room. The Bold comes in a range of 3 types: 10W, 25W and 35W. Possible RAL colours: 9005 and 9010. Available in 3000K and 4000K. Standard on/off, dimmable in Triac.

Reference : 000002234