

WINK

9005 Chroom zwart 2700K/CRI90 15° triac



Beamangle	15°	Input current	350mA
CIE Flux Codes	78 96 99 100 100	IP	IP33
Colour Deviation (SDCM)	3 sdcM	Color	RAL9005
Colour Temperature	2700K	Color 2	Chrome black
Max. connected Load	7W	Led type	SMD
Connected Voltage	220-240V	Lumen Maintenance	L80B10 bij 50.000
CRI	90	Lumen/W	135lm/W
Cut Out Dimensions	Ø45-50	Luminous flux of luminaire	700lm
Dim		Material Housing	Aluminium
Dimensions	Ø40x90	Material Lens/Reflector/Diffusor	PC
Energy Efficiency Class	D	Mounting Type	Recessed
Forward Voltage	18V	PF	0,9
Frequency	50-60Hz	UGR	<19
IK	05	Weight	300g

Reference : 000004447

Product Description

Spot lighting with character. Personalise the Wink by choosing a specific colour for the inner ring and outer ring, 576 variations to make your interior shine. The body is available in RAL9005 & RAL9010, the inner ring is available in 9005, 9010, Gold, Silver, Chrome and Chrome Black. The multitude of colours makes this LED spotlight suitable for any type of space where subtlety and design are paramount. Dimensions: Ø40x90. Choose your favourite beam angle (15°, 24°, 38° or 50°) and accentuate the space for an architectural touch. Available in 27000K, 3000K and 4000K. Standard in on/off, dimmable possible in dali, triac or 1-10V. Wide range of applications in spaces where accent lighting and design are paramount. From residential to office lighting.