

WINK

9005 9010 4000K/CRI90 24° 1-10V



| | | | |
|-------------------------|------------------|----------------------------------|-------------------|
| Beamangle | 24° | Input current | 350mA |
| CIE Flux Codes | 78 96 99 100 100 | IP | IP33 |
| Colour Deviation (SDCM) | 3 sdcM | Color | RAL9005 |
| Colour Temperature | 4000K | Color 2 | RAL9005 |
| Max. connected Load | 7W | Led type | SMD |
| Connected Voltage | 220-240V | Lumen Maintenance | L80B10 bij 50.000 |
| CRI | 90 | Lumen/W | 135lm/W |
| Cut Out Dimensions | Ø45-50 | Luminous flux of luminaire | 700lm |
| Dim | 1-10V | Material Housing | Aluminium |
| Dimensions | Ø40x90 | Material Lens/Reflector/Diffusor | PC |
| Energy Efficiency Class | D | Mounting Type | Recessed |
| Forward Voltage | 18V | PF | 0,9 |
| Frequency | 50-60Hz | UGR | <19 |
| IK | 05 | Weight | 300g |

Reference : 000004572

Product Description

Spot lighting with character. Personalise the Wink by choosing a specific colour for the inner ring and outer ring, 576 variations to make your interior shine. The body is available in RAL9005 & RAL9010, the inner ring is available in 9005, 9010, Gold, Silver, Chrome and Chrome Black. The multitude of colours makes this LED spotlight suitable for any type of space where subtlety and design are paramount. Dimensions: Ø40x90. Choose your favourite beam angle (15°, 24°, 38° or 50°) and accentuate the space for an architectural touch. Available in 27000K, 3000K and 4000K. Standard in on/off, dimmable possible in dali, triac or 1-10V. Wide range of applications in spaces where accent lighting and design are paramount. From residential to office lighting.