

# WINK

9010 9010 3000K/CRI90 38° on/off



CIE Flux Codes	78 96 99 100 100	IP	IP33
Colour Deviation (SDCM)	3 sdcM	Color	
Max. connected Load	7W	Color 2	
Connected Voltage	220-240V	Led type	SMD
CRI	90	Lumen Maintenance	L80B10 bij 50.000
Cut Out Dimensions	Ø45-50	Lumen/W	135lm/W
Dim		Luminous flux of luminaire	700lm
Dimensions	Ø40x90	Material Housing	Aluminium
Energy Efficiency Class	D	Material Lens/Reflector/Diffusor	PC
Forward Voltage	18V	Mounting Type	Recessed
Frequency	50-60Hz	PF	0,9
IK	05	UGR	<19
Input current	350mA	Weight	300g

## Product Description

Spot lighting with character. Personalise the Wink by choosing a specific colour for the inner ring and outer ring. 576 variations to make your interior shine. The body is available in RAL9005 & RAL9010, the inner ring is available in 9005, 9010, Gold, Silver, Chrome and Chrome Black. The multitude of colours makes this LED spotlight suitable for any type of space where subtlety and design are paramount. Dimensions: Ø40x90. Choose your favourite beam angle (15°, 24°, 38° or 50°) and accentuate the space for an architectural touch. Available in 2700K, 3000K and 4000K. Standard in on/off, dimmable possible in dali, triac or 1-10V. Wide range of applications in spaces where accent lighting and design are paramount. From residential to office lighting.

Reference : 000004966