



# GLOW 120

9016 3000K/CRI80 on/off Direct



Beamangle	120	IP	IP44
CIE Flux Codes	49 80 96 99 100	Color	RAL9016
Colour Deviation (SDCM)	3 sdc	Led type	SMD
Colour Temperature	3000K	Lichtuittreding	Direct
Max. connected Load	150W	Lumen Maintenance	L80B10 bij 50.000
Connected Voltage	220-240V	Lumen/W	135lm/W
CRI	85	Luminous flux of luminaire	13000lm
Dim	No	Material Housing	Diecast aluminium
Dimensions	Ø1200x105	Material Lens/Reflector/Diffusor	PMMA
Energy Efficiency Class	D	Mounting Type	Ceiling
Forward Voltage	35-42V	PF	0,9
Frequency	50-60Hz	Protection Class	I
IK	05	UGR	<24
Input current	3570mA	Weight	15kg

Reference : 000002977

## Product Description

A minimalist design with a high eye-catcher content makes the Glow a product that you can do anything with. Play with sizes for an unseen atmosphere or mix-and-match with the Ring for a spectacle of lighting. Ambient lighting in efficiency, an eye-catcher in your interior. The high design level and the possibility to combine with other eye-catchers make this downlighter a much sought-after product in hospitality, retail, office spaces and public spaces that must stand out. Available in four types: 45 (Dimensions: 450x105), 60 (Dimensions: 600x105), 90 (Dimensions: 900x105), 120 (Dimensions: 1200x105). Available in 3000K or 4000K. Standard on/off. Dimmable in dali, dali push, triac and 1-10V. This panel is available in RAL9005 and RAL9016.