


RING 90




3000K/CRI80



















Beamangle	120	IP	IP22
CIE Flux Codes	49 80 96 99 100	Color	
Colour Deviation (SDCM)	3 sdcm	Led type	SMD
Colour Temperature		Lumen Maintenance	L80B10 bij 50.000
Max. connected Load	72W	Lumen/W	135lm/W
Connected Voltage	220-240V	Luminous flux of luminaire	6000lm
CRI	80	Material Housing	Diecast aluminium
Dim		Material Lens/Reflector/Diffusor	PMMA
Dimensions	Ø900x105	Mounting Type	Suspension
Forward Voltage	42V	PF	0,9
Frequency	50-60Hz	Protection Class	I
IK	05	Suspension Length	1,5m/4m
Input current	1800mA	UGR	<24

Reference: 000004292

Product Description

Eye-catcher with a breathtakingly high design content. Play with sizes for an unseen atmosphere or mix-and-match with the Glow for a spectacle of light. Ambient lighting in efficiency, an eye-catcher in your interior. Because of the high design content and the possibility to combine with other eye-catchers, this downlighter is a much sought-after product in hospitality, retail, office spaces and public spaces that must stand out. Available in three types 60 (Dimensions: 600x105), 90 (Dimensions: 900x105), 120 (Dimensions: 1200x105). Available in 3000K or 4000K. Standard on/off. Dimmable in dali, dali push, triac and 1-10V. This circular luminaire is available in RAL9005 and RAL9016.