





OCULI

9005 9016 4000K/CRI80 45° triac



Beamangle	45°	IK	02
CIE Flux Codes	96 99 100 100 100	Input current	350mA
Colour Deviation (SDCM)	3 sdcn	IP	IP33
Colour Temperature	4000K	Color	RAL9005
Max. connected Load	5W	Color 2	RAL9016
Connected Voltage	220-240V	Led type	SMD
CRI	>90	Lumen Maintenance	L80B10 bij 50.000
Dim	Triac	Lumen/W	135lm/W
Dimensions	228x54x70	Luminous flux of luminaire	500lm
ENEC	Ja	Material Housing	Aluminium
Energy Efficiency Class	D	Material Lens/Reflector/Diffusor	PMMA
Forward Voltage	15V	Mounting Type	Ceiling
Frequency	50-60Hz	PF	0,9
Glow Wire Test	650°C	Protection Class	I
		UGR	<25

Product Description

Together with the Argus, the Oculi is the most architectural accent lighting in a surface-mounted luminaire. This subtle bulb guarantees optimal accent lighting. The silky-smooth finish with a touch of glam provides ideal ambient lighting in any room. Manifested as a surface-mounted luminaire, praised for its design. Choose 15°, 25°, 45° depending on the space you want to illuminate. Available in 3000K or 4000K. Dimensions: 228x54x70. Standard on/off. Dimmable in dali, dali push and 1-10V. Colours housing: RAL9005, RAL9010, RAL9016 and aluminium. Colour choices cover: RAL9005, RAL9010 and RAL9016.

Reference : 000023612