





# OCULI

Aluminium 9010 3000K/CRI80 45° triac



|                         |                   |                                  |                   |
|-------------------------|-------------------|----------------------------------|-------------------|
| Beamangle               | 45°               | IK                               | 02                |
| CIE Flux Codes          | 96 99 100 100 100 | Input current                    | 350mA             |
| Colour Deviation (SDCM) | 3 sdcM            | IP                               | IP33              |
| Colour Temperature      | 3000K             | Color                            | Aluminium         |
| Max. connected Load     | 5W                | Color 2                          | RAL9010           |
| Connected Voltage       | 220-240V          | Led type                         | SMD               |
| CRI                     | >90               | Lumen Maintenance                | L80B10 bij 50.000 |
| Dim                     | Triac             | Lumen/W                          | 135lm/W           |
| Dimensions              | 228x54x70         | Luminous flux of luminaire       | 500lm             |
| ENEC                    | Ja                | Material Housing                 | Aluminium         |
| Energy Efficiency Class | D                 | Material Lens/Reflector/Diffusor | PMMA              |
| Forward Voltage         | 15V               | Mounting Type                    | Ceiling           |
| Frequency               | 50-60Hz           | PF                               | 0,9               |
| Glow Wire Test          | 650°C             | Protection Class                 | I                 |
|                         |                   | UGR                              | <25               |

## Product Description

Together with the Argus, the Oculi is the most architectural accent lighting in a surface-mounted luminaire. This subtle bulb guarantees optimal accent lighting. The silky-smooth finish with a touch of glam provides ideal ambient lighting in any room. Manifested as a surface-mounted luminaire, praised for its design. Choose 15°, 25°, 45° depending on the space you want to illuminate. Available in 3000K or 4000K. Dimensions: 228x54x70. Standard on/off. Dimmable in dali, dali push and 1-10V. Colours housing: RAL9005, RAL9010, RAL9016 and aluminium. Colour choices cover: RAL9005, RAL9010 and RAL9016.

Reference : 000023657