


FL Vierkant 3030

4000K/CRI80 EM. 1h DALI 9005



Beamangle	120	IK	07
CIE Flux Codes	47 78 95 100 100	IP	IP54
CRI	80	Input current	700mA
Colour Deviation (SDCM)	3 sdcM	Color	RAL9005
Colour Temperature	4000K	Led type	SMD
Max. connected Load	24W	Lumen Maintenance	L80B10 bij 50.000
Connected Voltage	220-240V	Lumen/W	135lm/W
Cut Out Dimensions	295x295	Luminous flux of luminaire	2400lm
Dim	1h Dali	Material Housing	Diecast aluminium
Dimensions	315x315x18	Material Lens/Reflector/Diffusor	PMMA
Energy Efficiency Class	D	Mounting Type	Inbouw
Forward Voltage	33-40V	PF	0,9
Frequency	50-60Hz	Protection Class	I
		UGR	19

Product Description

Modern panel for suspended ceilings. The FL ensures that a surface is optimally lit without being obtrusive. Thanks to an ingenious system, the panel blends into the room so that the system ceiling remains very taut. The interesting UGR (UGR19) makes the FL a much sought-after panel for office spaces and corridors. The FL square is available in 15W & 24W. Dimensions: 172x172 (15W) or 300x300 (35W). Available in 3000K or 4000K. Standard on/off. Dimmable in dali, dali push, triac and 1-10V. This panel is available in RAL9005 and RAL9016.

Reference : 000027711