


FL Vierkant 3030

9016 4000K/CRI80 EM. 1h ST on/off



Beamangle	120	IK	07
CIE Flux Codes	47 78 95 100 100	Input current	700mA
Colour Deviation (SDCM)	3 sdcn	IP	IP54
Colour Temperature	4000K	Color	RAL9016
Max. connected Load	24W	Led type	SMD
Connected Voltage	220-240V	Lumen Maintenance	L80B10 bij 50.000
CRI	80	Lumen/W	135lm/W
Cut Out Dimensions	295x295	Luminous flux of luminaire	2400lm
Dim	1h ST	Material Housing	Diecast aluminium
Dimensions	315x315x18	Material Lens/Reflector/Diffusor	PMMA
Energy Efficiency Class	D	Mounting Type	Recessed
Forward Voltage	33-40V	PF	0,9
Frequency	50-60Hz	Protection Class	I
		UGR	19

Reference : 000027714

Product Description

Modern panel for suspended ceilings. The FL ensures that a surface is optimally lit without being obtrusive. Thanks to an ingenious system, the panel blends into the room so that the system ceiling remains very taut. The interesting UGR (UGR19) makes the FL a much sought-after panel for office spaces and corridors. The FL square is available in 15W & 24W. Dimensions: 172x172 (15W) or 300x300 (35W). Available in 3000K or 4000K. Standard on/off. Dimmable in dali, dali push, triac and 1-10V. This panel is available in RAL9005 and RAL9016.