


MAMBA STRIBE 150 PENDEL

9016 9016 3000K/CRI90 Casambi



| | | | |
|-------------------------|-----------------|----------------------------------|-------------------|
| Beamangle | 120 | IP | IP33 |
| CIE Flux Codes | 49 80 95 99 100 | Color | RAL9016 |
| Colour Deviation (SDCM) | 3 sdc | Color 2 | RAL9016 |
| Colour Temperature | 3000K | Led type | SMD |
| Max. connected Load | 35W | Lumen Maintenance | L80B10 bij 50.000 |
| Connected Voltage | 220-240V | Lumen/W | 135lm/W |
| CRI | 90 | Luminous flux of luminaire | 3500lm |
| Dim | Casambi | Material Housing | Aluminium |
| Dimensions | Ø42x1590 | Material Lens/Reflector/Diffusor | PMMA |
| Energy Efficiency Class | D | Mounting Type | Suspension |
| Forward Voltage | 42V | PF | 0,98 |
| Frequency | 50-60Hz | Protection Class | II |
| IK | 07 | Suspension Length | 1,5m |
| Input current | 350mA | UGR | <23 |

Reference : 000028603

Product Description

The Mamba also combines the most Lednlux recognizable roundings found elsewhere within our range. Together with a subtle look and straightforwardness. A clever piece of design work that is best expressed as a statement piece in the midst of everyone's interior. What the mamba is mainly about are the modular magnetic coupling modules implemented in each component. By combining this with a 48V system and the latest LED technologies, we were able to keep the power supply so low that a slim design did not present any development problems. Due to the dynamics between the magnetic coupling modules, all components can be rotated 360° around its axis as well as individually rotated 180° horizontally, allowing the end to become the beginning. Configuring a mamba fixture is done entirely and only at your request. From a sleek fixture above your dining table to a composition that results in virtually endless combination possibilities.