



MAMBA KUPS 150 PENDEL





























| Beamangle | 15° | IP | IP33 |
|-------------------------|-------------------|----------------------------------|----------|
| CIE Flux Codes | 92 98 100 100 100 | Color | RAL90 |
| Colour Deviation (SDCM) | 3 sdcm | Color 2 | RAL901 |
| Colour Temperature | 3000K | Led type | SMD |
| ax. connected Load | 3x3W | Lumen Maintenance | L80B10 |
| onnected Voltage | 220-240V | Lumen/W | 135lm/V |
| RI | 90 | Luminous flux of luminaire | 900lm |
| im | Dali | Material Housing | Aluminiu |
| mensions | Ø42x1590 | Material Lens/Reflector/Diffusor | PMMA |
| ergy Efficiency Class | D | Mounting Type | Suspensi |
| orward Voltage | 27V | PF | 0,98 |
| requency | 50-60Hz | Protection Class | II |
| (| 07 | Suspension Length | 1,5m |
| Input current | 350mA | UGR | 16 |
| | | Weight | 4kg |

Reference: 000028830

Product Description

The Mamba also combines the most Lednlux recognizable roundings found elsewhere within our range. Together with a subtle look and straightforwardness. A clever piece of design work that is best expressed as a statement piece in the midst of everyone's interior. What the mamba is mainly about are the modular magnetic coupling modules implemented in each component. By combining this with a 48V system and the latest LED technologies, we were able to keep the power supply so low that a slim design did not present any development problems. Due to the dynamics between the magnetic coupling modules, all components can be rotated 360° around its axis as well as individually rotated 180° horizontally, allowing the end to become the beginning. Configuring a mamba fixture is done entirely and only at your request. From a sleek fixture above your dining table to a composition that results in virtually endless combination possibilities.