


# MAMBA KUPS 150 PENDEL

9010 9016 2700K/CRI90 45° Casambi



Beamangle	45°	IP	IP33
CIE Flux Codes	92 98 100 100 100	Color	RAL9010
Colour Deviation (SDCM)	3 sdcM	Color 2	RAL9016
Colour Temperature	2700K	Led type	SMD
Max. connected Load	3x3W	Lumen Maintenance	L80B10 bij 50.000
Connected Voltage	220-240V	Lumen/W	135lm/W
CRI	90	Luminous flux of luminaire	900lm
Dim	Casambi	Material Housing	Aluminium
Dimensions	Ø42x1590	Material Lens/Reflector/Diffusor	PMMA
Energy Efficiency Class	D	Mounting Type	Suspension
Forward Voltage	27V	PF	0,98
Frequency	50-60Hz	Protection Class	II
IK	07	Suspension Length	1,5m
Input current	350mA	UGR	16
		Weight	4kg

Reference : 000028934

## Product Description

The Mamba also combines the most Lednlux recognizable roundings found elsewhere within our range. Together with a subtle look and straightforwardness. A clever piece of design work that is best expressed as a statement piece in the midst of everyone's interior. What the mamba is mainly about are the modular magnetic coupling modules implemented in each component. By combining this with a 48V system and the latest LED technologies, we were able to keep the power supply so low that a slim design did not present any development problems. Due to the dynamics between the magnetic coupling modules, all components can be rotated 360° around its axis as well as individually rotated 180° horizontally, allowing the end to become the beginning. Configuring a mamba fixture is done entirely and only at your request. From a sleek fixture above your dining table to a composition that results in virtually endless combination possibilities.