


MAMBA KUPS 150 PENDEL





























15°	IP	IP33
92 98 100 100 100	Color	RAL9016
3 sdcm	Color 2	Gold
3000K	Led type	SMD
3x3W	Lumen Maintenance	L80B10 bij 50.000
220-240V	Lumen/W	135lm/W
90	Luminous flux of luminaire	900lm
Dali push	Material Housing	Aluminium
Ø42x1590	Material Lens/Reflector/Diffusor	PMMA
D	Mounting Type	Suspension
27V	PF	0,98
50-60Hz	Protection Class	II
07	Suspension Length	1,5m
350mA	UGR	16
	Weight	4kg
	92 98 100 100 100 3 sdcm 3000K 3x3W 220-240V 90 Dali push Ø42x1590 D 27V 50-60Hz 07	92 98 100 100 100 Color 3 sdcm Color 2 3000K Led type 3x3W Lumen Maintenance 220-240V Lumen/W 90 Luminous flux of luminaire Dali push Material Housing Ø42x1590 Material Lens/Reflector/Diffusor D Mounting Type 27V PF 50-60Hz Protection Class 07 Suspension Length 350mA UGR

Reference: 000029462

Product Description

The Mamba also combines the most Lednlux recognizable roundings found elsewhere within our range. Together with a subtle look and straightforwardness. A clever piece of design work that is best expressed as a statement piece in the midst of everyone's interior. What the mamba is mainly about are the modular magnetic coupling modules implemented in each component. By combining this with a 48V system and the latest LED technologies, we were able to keep the power supply so low that a slim design did not present any development problems. Due to the dynamics between the magnetic coupling modules, all components can be rotated 360° around its axis as well as individually rotated 180° horizontally, allowing the end to become the beginning. Configuring a mamba fixture is done entirely and only at your request. From a sleek fixture above your dining table to a composition that results in virtually endless combination possibilities.