

OKKO 10

9005 9010 2700K/CRI90 36° Casambi



Beamangle	36°	Color 2	RAL9010
CIE Flux Codes	96 99 100 100 100	Input current	500mA
Colour Deviation (SDCM)	3 sdcn	IP	IP33
Colour Temperature	2700K	Led type	COB
Max. connected Load	10W	Lumen Maintenance	L80B50 bij 100.000
Connected Voltage	220-240V	Lumen/W	135lm/W
CRI	90	Luminous flux of luminaire	1100lm
Dim	Casambi	Material Housing	Aluminium
Dimensions	Ø83x122	Material Lens/Reflector/Diffusor	Aluminium
Energy Efficiency Class	D	Mounting Type	in 3fase rail
Forward Voltage	33V	Color	RAL9005
Frequency	50Hz	PF	0,9
IK	06	UGR	19

Reference : 000029833

Product Description

The Okko is an efficiency monster in every sense of the word. Its versatility translates in many ways. The mounting method, the variety of colors and the modularity within the different lens rings are its greatest assets. On a technical level it doesn't drop a single stitch, its ingenious design makes it possible to control from 10 to 30W (1000-3000lm), so you can use the same fixture for many different purposes which forms a nice uniform line in your lighting concept. With the high quality Citizen led chip (CLU03j), standard CRI +90 and the Unique aluminum reflectors in the angles 23°, 36° and 60° it proves to excel far from all its competitors. This combined with Signify/Tridonic LED drivers and high-quality powder-coated components in both standard and on-demand colors make endless combinations possible. In addition, it also carries flexibility as a high priority. It is available in any RAL color, light color or power on request.