


QQU 20

























36°	Input current	500mA
96 99 100 100 100	IP	IP33
3 sdcm	Color	RAL9010
4000K	Color 2	Copper
20W	Led type	СОВ
220-240V	Lumen Maintenance	L80B10 bij 50.000
90	Lumen/W	135lm/W
Dali push	Luminous flux of luminaire	2000lm
Ø93x122	Material Housing	Aluminium
D	Material Lens/Reflector/Diffusor	Aluminium
33V	Mounting Type	in 3fase rail
50Hz	PF	0,9
06	UGR	19
	96 99 100 100 100 3 sdcm 4000K 20W 220-240V 90 Dali push Ø93x122 D 33V 50Hz	96 99 100 100 100 IP 3 sdcm Color 4000K Color 2 20W Led type 220-240V Lumen Maintenance 90 Lumen/W Dali push Luminous flux of luminaire Ø93x122 Material Housing D Material Lens/Reflector/Diffusor 33V Mounting Type 50Hz PF

Reference: 000030948

Product Description

Product Description

The Oqqo is an efficiency monster in every sense of the word. Its versatility translates in many ways. The mounting method, the variety of colors and the modularity within the different lens rings are its greatest assets. On a technical level it doesn't drop a single stitch, its ingenious design makes it possible to control from 10 to 30W (1000-3000lm), so you can use the same fixture for many different purposes which forms a nice uniform line in your lighting concept. nnWith the High quality Citizen led chip (CLU03)), standard CRI +90 and the Unique aluminum reflectors in the angles 23°, 36° and 60° it proves to excel far from all its competitors. This combined with Signify/Tridonic LED drivers and high quality powder coated components in both standard and on-demand colors make endless pairings available. In addition, it also carries Flexibility highly. It is available in any RAL color, light color or power on demand.