

WINK

9005 Goud 3000K/CRI90 38° 1-10V



Beamangle	38°	Input current	350mA
CIE Flux Codes	78 96 99 100 100	IP	IP33
Colour Deviation (SDCM)	3 sdcn	Color	RAL9005
Colour Temperature	3000K	Color 2	Gold
Max. connected Load	7W	Led type	SMD
Connected Voltage	220-240V	Lumen Maintenance	L80B10 bij 50.000
CRI	90	Lumen/W	135lm/W
Cut Out Dimensions	Ø45-50	Luminous flux of luminaire	700lm
Dim	1-10V	Material Housing	Aluminium
Dimensions	Ø40x90	Material Lens/Reflector/Diffusor	PC
Energy Efficiency Class	D	Mounting Type	Recessed
Forward Voltage	18V	PF	0,9
Frequency	50-60Hz	UGR	<19
IK	05	Weight	300g

Reference : 000004497

Product Description

L'éclairage spot de caractère. Personnalisez le Wink en choisissant une couleur spécifique pour l'anneau intérieur et l'anneau extérieur. 576 variations pour faire briller votre intérieur. Le corps est disponible en RAL9005 et RAL9010, l'anneau intérieur est disponible en 9005, 9010, or, argent, chrome et noir chrome. La multiplicité des couleurs rend ce spot LED applicable dans tout type d'espace où la subtilité et le design sont primordiaux. Dimensions : Ø40x90. Choisissez votre angle de rayonnement préféré (15°, 24°, 38° ou 50°) et accentuez l'espace pour une touche architecturale. Disponible en 27000K, 3000K et 4000K. Standard en marche/arrêt, dimmable possible en dali, triac ou 1-10V. Largement applicable dans les espaces où l'éclairage d'accentuation et le design sont primordiaux. De l'éclairage résidentiel à l'éclairage de bureau.