





BOLD 10

9005 4000K/CRI80 on/off



Beamangle	60°	IP	54
CIE Flux Codes	93 99 100 100 100	Input Current	250mA
CRI	90	Kleur	RAL9005
Colour Deviation (SDCM)	3 sdcm	Led type	COB
Colour Temperature	4000K	Lumen Maintenance	L80B10 bij 50.000
Connected Load	10W	Lumen/W	100lm/W
Connected Voltage	220-240V	Luminous flux of luminaire	1000lm
Dim	Nee	Material Housing	Aluminium
Dimensions	100x90	Material Lens/Reflector/Diffuser	Glas
Energy Efficiency Class	A+	Mounting Type	Opbouw
Forward Voltage	25V	PF	0,9
Frequency	50-60Hz	Protection Class	I
IK	02	UGR	<19
		Weight	400g

Product Description

De Bold zorgt net voor dat tikkeltje extra. Breng jouw ruimte tot leven en mix-and-match deze **krachtige downlighter**. Door de eenvoudige afwerking verfijnd met elegantie is de Bold buitengewoon **veelzijdig**. De krachtige lichtoutput zorgt voor een doelgerichte belichting. Het **cilindrisch design** zorgt ervoor dat de Bold in talrijke moderne woonstijlen tot haar recht komt. Zowel voor de commerciële markt als in de huiskamer. De Bold bestaat uit een range van 3 types: 10W, 25W en 35W. Mogelijke RAL-kleuren: 9005 en 9010. Beschikbaar in 3000K en 4000K. Standaard aan/uit, dimbaar in Triac.

Reference : 000002228