



BOLD 25

9005 3000K/CRI80 1-10V



Beamangle	60°	Kleur	RAL9005
CIE Flux Codes	85 99 100 100 100	Led type	COB
CRI	90	Lumen Maintenance	L80B10 bij 50.000
Colour Deviation (SDCM)	3 sdcm	Lumen/W	135lm/W
Colour Temperature	3000K	Luminous flux of luminaire	2500lm
Dim	1-10V	Material Housing	Aluminium
Dimensions	Ø110x120	Material Lens/Reflector/Diffusor	Glas
Energy Efficiency Class	D	Max. connected Load	25W
Forward Voltage	30-40V	Mounting Type	Opbouw
Frequency	50-60Hz	PF	0,9
IK	02	Protection Class	I
IP	IP54	UGR	<19
Input current	600mA	Voltage	220-240V
		Weight	800g

Product Description

De Bold zorgt net voor dat tikkeltje extra. Breng jouw ruimte tot leven en mix-and-match deze **krachtige downlighter**. Door de eenvoudige afwerking verfijnd met elegantie is de Bold buitengewoon **veelzijdig**. De krachtige lichtoutput zorgt voor een doelgerichte belichting. Het **cilindrisch design** zorgt ervoor dat de Bold in talrijke moderne woonstijlen tot haar recht komt. Zowel voor de commerciële markt als in de huiskamer. De Bold bestaat uit een range van 3 types: 10W, 25W en 35W. Mogelijke RAL-kleuren: 9005 en 9016. Beschikbaar in 3000K en 4000K. Standaard aan/uit, dimbaar in Triac.

Reference : 000002241