





FYRA

Aluminium 3000K/CRI80 1-10V



Beamangle	180°	Led type	SMD
CIE Flux Codes	53 82 97 99 100	Lumen Maintenance	L80B10 bij 50.000
Colour Deviation (SDCM)	3 sdcm	Lumen/W	100lm/W
Colour Temperature	3000K	Luminous flux of luminaire	4800lm
CRI	80	Material Housing	Aluminium
Dim	1-10V	Material Lens/Reflector/Diffusor	PMMA
Dimensions	990x970x20 & 485x470x20	Max. connected Load	2x5W
Energy Efficiency Class	A	Mounting Type	Inbouw
Forward Voltage	24V	PF	0,9
Frequency	50-60Hz	Protection Class	II
IK	07	UGR	<25
Kleur	Aluminium	Voltage	220-240V
		Weight	4kg

Reference : 000005045

Product Description

Architecturale lijnverlichting met een eigenzinnige toets. Deze decoratieve verlichting is een lust voor de ogen van elke designee. Door de verfijnde geometrische vormen is deze verlichting geschikt in openbare ruimtes, hallen en trappengangen. Beschikbaar in **plafond- en wandmontage**. Verkrijgbaar in RAL9005, RAL9010, RAL9016, aluminium of een RAL-kleur naar keuze. Mogelijke sturingen zijn dali, dali push, triac of aan/uit. Afmetingen: 990x970x20 & 485x470x20.