




KALI

9005 9005 2700K/CRI90 50° on/off



Beamangle	50°	Kleur 2	RAL9005
CIE Flux Codes	98 99 100 100 92	Led type	COB
Colour Deviation (SDCM)	3 sdcm	Lumen Maintenance	L80B10 bij 50.000
Colour Temperature	2700K	Lumen/W	135lm/W
CRI	90	Luminous flux of luminaire	1000lm
Cut Out Dimensions	Ø78	Material Housing	Aluminium
Dim	Nee	Material Lens/Reflector/Diffusor	PC
Dimensions	Ø84x81	Max. connected Load	10W
Energy Efficiency Class	D	Mounting Type	Inbouw
Forward Voltage	18-21V	PF	0,9
Frequency	50-60Hz	Protection Class	I
IK	05	Recess Depth	90
Input current	500mA	UGR	<19
IP	IP33	Voltage	230V
Kleur	RAL9005	Weight	250g

Reference : 000003062

Product Description

Deze zeer uitgesproken en tevens **personaliseerbare inbouwspot** is populair designees. Pimp jouw favoriete kleuren en laat jouw interieur stralen. 720 varianties maakt de KALI de meest veelzijdige inbouwspot. De body is verkrijgbaar in RAL9005 & RAL9010, de binnenring is verkrijgbaar in 9005, 9010, Goud, Zilver, Chroom en Chroom zwart. Door het veelvoud aan kleuren is deze ledspot toepasbaar in elke type ruimte waar subtiliteit en design primeert. Afmetingen: Ø84x81, inbouwmaat: Ø78. Kies jouw favoriete **stralingshoek** (15°, 24°, 38° of 50°) en accentueer de ruimte voor een architecturale touch. Beschikbaar in 27000K, 3000K en 4000K. Standaard in aan/uit, dimbaar mogelijk in dali, dali push, triac of 1-10V. Breed toepasbaar in ruimtes waar accentverlichting en design primeert. Van residentieel tot office lighting.