

WINK

9005 Chroom 2700K/CRI90 38° 1-10V



| | | | |
|-------------------------|------------------|----------------------------------|-------------------|
| Beamangle | 38° | Kleur | RAL9005 |
| CIE Flux Codes | 78 96 99 100 100 | Kleur 2 | Chroom |
| Colour Deviation (SDCM) | 3 sdcn | Led type | SMD |
| Colour Temperature | 2700K | Lumen Maintenance | L80B10 bij 50.000 |
| CRI | 90 | Lumen/W | 135lm/W |
| Cut Out Dimensions | Ø45-50 | Luminous flux of luminaire | 700lm |
| Dim | | Material Housing | Aluminium |
| Dimensions | Ø40x90 | Material Lens/Reflector/Diffuser | PC |
| Energy Efficiency Class | D | Max. connected Load | 7W |
| Forward Voltage | 18V | Mounting Type | Inbouw |
| Frequency | 50-60Hz | PF | 0,9 |
| IK | 05 | UGR | <19 |
| Input current | 350mA | Voltage | 220-240V |
| IP | IP33 | Weight | 300g |

Reference : 000004425

Product Description

Spotverlichting met karakter. **Personaliseer** de Wink door een specifieke kleur te kiezen voor de binnenring en buitenring. 576 variaties om jouw interieur te laten stralen. De body is verkrijgbaar in RAL9005 & RAL9010, de binnenring is verkrijgbaar in 9005, 9010, Goud, Zilver, Chroom en Chroom zwart. Door het veelvoud aan kleuren is deze ledspot toepasbaar in elke type ruimte waar subtiliteit en design primeert. Kies jouw favoriete stralingshoek (15°, 24°, 38° of 50°) en accentueer de ruimte voor een architecturale touch. Beschikbaar in 2700K, 3000K en 4000K. Standaard in aan/uit, dimbaar mogelijk in dali, triac of 1-10V. Breed toepasbaar in ruimtes waar accentverlichting en design primeert. **Van residentieel tot office lighting.**