

# WINK

9005 Zilver 2700K/CR190 50° Triac



Beamangle	50°	Kleur	RAL9005
CIE Flux Codes	78 96 99 100 100	Kleur 2	Zilver
Colour Deviation (SDCM)	3 sdcM	Led type	SMD
Colour Temperature	2700K	Lumen Maintenance	L80B10 bij 50.000
CRI	90	Lumen/W	135lm/W
Cut Out Dimensions	Ø45-50	Luminous flux of luminaire	700lm
Dim	Triac	Material Housing	Aluminium
Dimensions	Ø40x90	Material Lens/Reflector/Diffuser	PC
Energy Efficiency Class	D	Max. connected Load	7W
Forward Voltage	18V	Mounting Type	Inbouw
Frequency	50-60Hz	PF	0,9
IK	05	UGR	<19
Input current	350mA	Voltage	220-240V
IP	IP33	Weight	300g

Reference : 000004442

## Product Description

**Spotverlichting** met karakter. **Personaliseer** de Wink door een specifieke kleur te kiezen voor de binnenring en buitenring. 576 variaties om jouw interieur te laten stralen. De body is verkrijgbaar in RAL9005 & RAL9010, de binnenring is verkrijgbaar in 9005, 9010, Goud, Zilver, Chroom en Chroom zwart. Door het veelvoud aan kleuren is deze ledspot toepasbaar in elke type ruimte waar subtiliteit en design primeert. Kies jouw favoriete stralingshoek (15°, 24°, 38° of 50°) en accentueer de ruimte voor een architecturale touch. Beschikbaar in 27000K, 3000K en 4000K. Standaard in aan/uit, dimbaar mogelijk in dali, triac of 1-10V. Breed toepasbaar in ruimtes waar accentverlichting en design primeert. **Van residentieel tot office lighting.**