


OCULI

9016 | 9010 | 4000K/CRI80 | 25° | Triac

Beamangle	25°	IP	IP33
CIE Flux Codes	96 99 100 100 100	Kleur	RAL9016
Colour Deviation (SDCM)	3 sdcm	Kleur 2	RAL9010
Colour Temperature	4000K	Led type	SMD
CRI	>90	Lumen Maintenance	L80B10 bij 50.000
Dim	Triac	Lumen/W	135lm/W
Dimensions	228x54x70	Luminous flux of luminaire	500lm
ENEC	Ja	Material Housing	Aluminium
Energy Efficiency Class	D	Material Lens/Reflector/Diffusor	PMMA
Forward Voltage	15V	Max. connected Load	5W
Frequency	50-60Hz	Mounting Type	Opbouw
Glow Wire Test	650°C	PF	0,9
IK	02	Protection Class	I
Input current	350mA	UGR	<25
		Voltage	220-240V

Reference : 000023641

Product Description

Together with the Argus, the Oculi is the most architectural accent lighting in a surface-mounted luminaire. This subtle bulb guarantees optimal accent lighting. The silky-smooth finish with a touch of glam provides ideal ambient lighting in any room. Manifested as a surface-mounted luminaire, praised for its design. Choose 15°, 25°, 45° depending on the space you want to illuminate. Available in 3000K or 4000K. Dimensions: 228x54x70. Standard on/off. Dimmable in dali, dali push and 1-10V. Colours housing: RAL9005, RAL9010, RAL9016 and aluminium. Colour choices cover: RAL9005, RAL9010 and RAL9016.

http://www.lednlux.be
BE0820044532

Slamstraat 1
3600 Genk - BE

+32 89 25 44 55
info@lednlux.be